

# SAFETY DATA SHEET

Chrome Roller Cleaner and Desensitizer - PCN 3462Q

SDS No. B0024

Date: 1/1/17

## Section 1 – Identification of the Mixture and Supplier

**Product Name:** Chrome Roller Cleaner and Desensitizer #3462Q

**SDS Number:** B0024

**CAS Number:** Mixture-Not Established

**Product Description:** Cleaner and Protective Coating for Printing Equipment Rollers

**Manufacturer/Supplier:** Burnishine Graphic Products, 25392 West Park Court, Lake Villa, IL 60046,

**Phone:** 847-356-0222, FAX 847-306-3550, WORK HOURS 8-5 (CST)

**EMERGENCY PHONE NUMBER:** (Infotrac) 800-535-5053 or 352-323-3500

## Section 2 – Hazard Identification

### GHS Classification of the Substance or Mixture

Health	Environmental	Physical
Skin Irritant – Category 2 Respiratory Tract Irritant – Category 3 Serious Eye Irritant – Category 2A Acute Toxicity/Oral- Category 4 Acute Toxicity/Inhalation – Category 5	None Known	Flammable Liquid - Category 3

### GHS Label Elements



**Signal Word: Warning**

### Hazard Statements:

**H200s = Physical H300s = Health H400s = Environmental**

- H226 Flammable liquid and vapor
- H302 Harmful if swallowed
- H315 Causes skin irritation
- H319 Causes serious eye irritation or damage
- H333 May be harmful if inhaled
- H335 May cause respiratory irritation

### Precautionary Statements:

**P200s = Prevention P300s = Response P400s = Storage P500s = Disposal**

- P210 Keep away from heat/sparks/open flames/hot surfaces-No Smoking
- P261 Avoid breathing fumes/mists/ vapors/ or spray
- P264 Wash hands thoroughly after handling
- P270 Do not eat/drink/or smoke when using this product
- P271 Use only in a well ventilated area
- P280 Wear protective gloves/clothing/and eye/face protection
- P301+312 If swallowed: call a poison center or doctor/physician if you feel unwell/rinse mouth with plenty of water
- P302+352 If on skin: wash with plenty of soap and water
- P332+313 If skin irritation occurs: get medical advice/attention
- P362 Take off contaminated clothing and wash before reuse
- P305+351+338 If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+313 If eye irritation persists: get medical advice/attention
- P304+340 If inhaled: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P304+312 If inhaled: call a poison center or doctor/physician if you feel unwell
- P370+378 In case of fire use water spray/dry chemical/carbon dioxide/alcohol foam
- P403+233 Store in a well-ventilated place. Keep container tightly closed
- P403+235 Store in well-ventilated place/keep cool
- P501 Dispose of contents/containers according to local regulations

### HMIS

**Health -2  
Fire -2  
React -0**

**PPE† Sec.8**

**Section 3 – Composition / Information on Ingredients**

Ingredient Name	CAS No.	% WT.
Water	7732-18-5	50-75
Glycol Ether EB	111-76-2	3-10
Ethylene Glycol	107-21-1	2-10
Isoparaffinic Hydrocarbon	64742-48-9	2-7
Phosphoric Acid	7664-38-2	1-2

**Section 4 - First Aid Measures**

**Inhalation:** Nasal irritation, nausea, dizziness, coughing, headache, shortness of breath, weakness, discoloration of face. Remove person from source of exposure to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if person is not breathing. GET IMMEDIATE MEDICAL ATTENTION.

**Skin Contact:** Itching, redness or burning of skin. Immediately flush skin thoroughly with plenty of water for several minutes and then wash skin with soap and water. Remove contaminated clothing and wash before reuse. If skin irritation persists, GET IMMEDIATE MEDICAL ATTENTION.

**Eye Contact:** Eye irritation. Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Remove contact lenses if present and easy to do. Continue Rinsing. If eye irritation persists, GET IMMEDIATE MEDICAL ATTENTION.

**Ingestion:** Irritation of the mouth and throat. Abdominal pain and nausea. Do not induce vomiting. If person is conscious, rinse mouth or give them a glass of water. If person is drowsy or unconscious and vomiting, place person on the left side with head down. GET MEDICAL ATTENTION IMMEDIATELY.

**Note to Physicians:** Treat Symptoms

**Special Precautions/Procedures:** After first-aid, get appropriate in-plant, paramedic, or community medical support.

See Section 11 for more detailed information on health effects and symptoms.

**Section 5 - Fire-Fighting Measures**

**Extinguishing Media:** Water spray, dry chemical, carbon dioxide, and alcohol foam.

**Unusual Fire or Explosion Hazards:** Combustible liquid. This product contains combustible organic components creating ignitable vapors when containers are heated. Heated vapors may be ignited by flames or sparks. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air and may travel long distances along ground before igniting.

**Hazardous Combustion Products:** Product may react with some metals (Aluminum, Zinc, Tin) to release hydrogen gas.

**Fire-Fighting Instructions:** Combustible liquid. Extinguish all sources of ignition. Keep away from heat, sparks, and flames. Use extinguishing media appropriate for surrounding fire. Use water spray to cool nearby containers and structures exposed to fire. Do not release runoff from fire control methods to sewers or waterways. Keep personnel removed and upwind.

**Fire-Fighting Equipment:** Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode with full protective clothing.

<b>NFPA</b>
<b>Health – 2</b>
<b>Fire – 2</b>
<b>React – 0</b>
<b>Hazards- Combustible</b>

**Section 6 - Accidental Release Measures**

**Personal Precautions:** Wear appropriate personal protective equipment as conditions warrant. (Review Section 8) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Follow all precautions for handling spill. (Review Section 7) Isolate spill or leak area and deny entry of untrained personnel.

**Emergency Procedures:** Isolate spill or leak. Eliminate all ignition sources. No smoking, flares, sparks, or flames in spill area. Ventilate spill area if fumes are present, keep unauthorized personnel away. Stay up-wind of any fumes.

**Spill/Leak Containment and Cleanup:** All equipment used when handling the spill must be grounded or non-sparking tools. Stop leak if you can do it without risk. Small spills: take up with sand or other non-combustible absorbent material and place into approved containers for later disposal. Large spills: dike area with non-combustible absorbent material to contain spill. Prevent spill from entering sewers, waterways, or low areas. Transfer spilled liquid and diking material to suitable approved containers for recovery or disposal. Do not flush spilled material into a sewer. Neutralize remaining spilled material with a diluted solution of acid if the spilled material is an alkaline or a diluted solution caustic if the spilled material is acidic. Clean up residue with soap and water. Do not flush to sewer or waterways. Prevent release into the environment.

**Refer to Section 13 for Proper Disposal of Spilled Material**

**Regulatory Requirements:** Any environmental release of a material that could cause harm to people or to the environment must be reported immediately to the National Response Center (NRC) and to the appropriate state and local agencies.

**Section 7 - Handling and Storage**

**Handling Precautions:** This is a combustible product and should be used with caution. Do not get in eyes, skin, or on clothing. Harmful if inhaled, absorbed through skin or swallowed. Prevent possible eye and skin contact by wearing the recommended protective clothing and equipment. Wash thoroughly after handling. Remove contaminated clothing after use. Do not breathe vapors or mist. Do not ingest. Do not cut, grind, puncture, drill, or weld near or expose containers to heat, flames, or other sources of ignition. Keep containers closed when not in use. Vapors are combustible to open flames. Vapors may accumulate and travel to distant ignition sources and flash back. Do not use pressure to empty containers. Always loosen closure cautiously when opening. Use in an area that will allow for evaporation to run off. Prevent soil contamination and entry into storm and floor drains, streams, and into any body of water.

**Storage Requirements:** Combustible liquid. Store in a cool, dry, well-vented area away from direct sunlight, heat, flames and sparks in a controlled environment. Do not store near combustible materials or liquids. Do not store in open unlabeled or mislabeled containers. Empty containers retain product vapor or residue. Follow all label warnings even after container is empty. Keep from freezing. Keep out of reach of children.

**Section 8 - Exposure Controls / Personal Protection**

Exposure Limits / Guidelines Ingredient Name	OSHA PEL	ACGIH TLV
Water	None Estab.	None Estab.
Glycol Ether EB	50 ppm	20 ppm
Ethylene Glycol	125 mg/m <sup>3</sup>	100 mg/m <sup>3</sup>
Isoparaffinic Hydrocarbon	500 ppm	100 ppm
Phosphoric Acid	1 mg/m <sup>3</sup>	3 mg/m <sup>3</sup>

**Engineering Controls for Ventilation:** Ensure good general ventilation. Use local exhaust ventilation to draw spray, mists, and vapors away from work area to prevent inhalation of product fumes. Provide general or local exhaust ventilation systems using corrosive resistant materials to maintain airborne contaminants below any recommended or standard occupational exposure limits. Local exhaust ventilation is preferred because it prevents contamination dispersion into the work area by controlling it at its source. Ventilation guidelines may be found in OSHA Regulations (29 CFR 1910.94) or in publications such as: American Conference of Governmental Industrial Hygienist.

**PERSONAL PROTECTIVE EQUIPMENT**

**Respiratory Protection:** If using in a confined area and fumes are present, use a respirator. None required under normal conditions of use if maintaining airborne contaminant concentrations below standard occupational exposure limits. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH – approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessel, or storage tanks) wear an SCBA. **Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

**Eye Protection:** Wear chemical safety goggles per OSHA eye and face protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of or in conjunction with contact lenses. Have an eye wash station available where eye contact can occur.

**Skin Protection:** Wear chemically protective gloves that are impervious to conditions of use. Use neoprene, nitrile, or butyl type rubber gloves. Additional protection may be necessary to prevent skin contact, including use of an apron, face shields, boots, or full body protection. A safety shower should be located in the general work area.

**General Hygiene:** Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Launder contaminated work clothes before reuse and keep personal protective equipment clean

## Section 9 - Physical and Chemical Properties

**Appearance:** Muddy Blue Liquid

**Odor:** Slight Solvent Odor

**pH:** 7.0-8.0

**Freeze Point:** Estimated at 20°F (-7°C)

**Boiling Point:** Estimated at 212°F (100°C)

**Odor Threshold:** Not Determined

**Vapor Pressure:** Not Determined

**Vapor Density (Air=1):** Not Determined

**Specific Gravity (H<sub>2</sub>O=1, at 72°F (22°C):** 1.01

**Water Solubility:** Partial

**Flash Point:** Estimated at 127°F

**Upper/Lower Flammability:** Not Determined

**Auto Ignition Temp:** Not Determined

**Evaporation Rate(Water=1):** Not Determined

**Partition Coefficient, N-Octanol/Water:**

**Decomposition Rate:** Not Determined

**Viscosity:** Estimated at 72°F Water-Like

**Voc Content:** 23.6%

## Section 10 - Stability and Reactivity

**Reactivity:** No dangerous reactions under normal conditions of use.

**Chemical Stability:** Stable in a controlled environment away from direct sunlight and stored at ambient temperatures.

**Hazard Reactions:** Hazardous reactions will not occur.

**Conditions to Avoid:** Combustible liquid. Avoid using or storing product in elevated temperatures or near heat, sparks, open flames or ignition sources. Prolonged contact with metals could produce small amounts of flammable hydrogen gas.

**Incompatible Materials:** Strong oxidizers, reducing agents and acids.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, and other toxic gases.

## Section 11 - Toxicological Information

\*Specific tests have not been conducted on this product. Our evaluations based on information from similar products, the ingredients and technical literature. Data for this material has been used to estimate the symptoms and effects of exposure.

**Eyes** Eye contact with liquid or mist can cause severe irritation. Which may result in temporary blurred vision.

**Skin** Skin LD50: Not established/ No data  
Brief contact would cause minimal irritation to the skin. Prolonged contact may cause moderate skin irritation. This product is not known to be a sensitizer.

**Inhalation** Inhalation LC50: Not established/ No data  
The product is not expected to present a significant inhalation hazard if work area is properly ventilated. Prolonged inhalation of vapors, mists, or fumes will cause irritation of respiratory tract creating headaches, nausea, weakness, and drowsiness.

**Ingestion** Oral LD50: Not established/ No data  
Ingestion is not regarded as significant health hazard likely to arise from normal use. Ingestion will cause severe irritation to digestive tract. Abdominal pain, nausea, vomiting and diarrhea will likely occur. Aspiration Hazard.

**Chronic Toxicity** There are no reports of long-term adverse toxic effects in man attributable to the use of this type of product. The product does contain ingredients, or which are derived from components, that potentially may affect the following target organs: eyes, skin, and respiratory system, liver, kidneys, and central nervous system.

**Carcinogenicity** IARC, NTP, and OSHA do list a few of the ingredients as a possible A2 carcinogen. Silica Crystalline Quartz (14808-60-7) Sodium 2-Biphenylate (132-27-4). ACGIH Lists Glycol Ether EB as an "A3" confirmed animal carcinogen with unknown relevance to humans.

<b>Mutagenicity</b>	There are no reports of mutagenic effects attributable to the use of this type of product or from its ingredients.
<b>Reproductive Toxicity</b>	There are no reports of reproductive effects attributable to the use of this type of product or from its ingredients. Ingredient Ethylene Glycol (107-21-1) has caused teratogenic and fetotoxic effects in rats and mice.

## Section 12 - Ecological Information

**\*Specific tests have not been conducted on this product. Our evaluation is based on information from similar products, the ingredients and technical literature. This information should be used only for a small truck spill and not meant to address discharges to sewers or treatment plants. Data for this material has been used to estimate its environmental impact.**

**Toxicity:** This material has a moderate potential for toxicity. Moderate biochemical oxygen demand and moderate potential to cause oxygen depletion in aqueous systems. A moderate potential to affect aquatic organisms.

**Environmental Degradation:** This product is readily biodegradable when diluted with large amounts of water, this material released into the environment is not expected to have a significant impact. (Minimum of 50 parts water to 1 part product). A low potential to persist in the environment.

**Soil Absorption/ Mobility:** This material is expected to be mobile in soil and not expected to absorb to suspended solids or sediments in water. A moderate potential to affect plant life.

## Section 13 - Disposal Considerations

**Waste Disposal Methods:** As sold, this product when discarded or disposed of is a non-hazardous waste. The transportation, storage, treatment, and disposal of this waste material must be conducted in compliance with (40CFR 261, 262, 263, 264, 268, and 270). Do not discharge this material into lakes, streams, ponds, or other waters. Do not discharge this material into sewer systems without the approval from local sewage treatment plant authority. Care must be taken to prevent environmental contamination from the use of this material. If material is not approved to be discharged into sewer system, contact a licensed waste management contractor for detailed recommendations for disposal. Follow all applicable Federal, state, and local regulations. This non-hazardous liquid can be incinerated if it meets all OSHA and EPA regulations. Incinerate at a licensed waste disposal site with approved environmental authority. If this product is altered, it is the responsibility of the user to determine whether the material meets the criteria for hazardous waste at the time of disposal.

**Disposal Regulatory Requirements:** Follow applicable NRC, CERCLA, SARA, and RCRA regulations.

**Container Cleaning and Disposal:** Prior to cleaning or disposing of container, use caution when handling empty container (possible combustible vapors). Do not use pressure to empty containers. Empty containers retain product vapors or residue that could be combustible. Follow all label warnings even after container is empty. Do not cut, weld, braze, solder, drill, grind, or expose empty containers to heat, flames or other sources of ignition. Follow applicable Federal, state, and local OSHA and EPA regulations.

## Section 14 - Transportation Information

### **U.S. Road Transportation DOT Data (49 CFR 172.101):**

Not regulated as a Hazardous Material or Dangerous Goods.

### **Canadian Road Transportation (TDG):**

Review Canadian Road Transportation (TDG) to determine if this product, for the packaging sizes being shipped, is considered dangerous goods. If this product is considered dangerous goods it may only require special labeling and proper shipping description.

### **Ocean Transportation (IMO/IMDG):**

Review Ocean Transport Regulations to determine if this product, for the packaging sizes being shipped, is considered dangerous goods. If this product is considered dangerous goods it may only require special labeling and proper shipping description.

### **Air Transportation (ICAO/IATA):**

Review Air Transportation Regulations to determine if this product, for the packaging sizes being shipped, is considered dangerous goods. IF this product is considered dangerous goods it may only require special labeling and proper shipping description.

**Section 15 - Regulatory Information**

**U.S. Federal Regulations**

**Toxic Substance Control Act (TSCA) Inventory Status:**

The components for this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

**Super Fund Amendments & Reauthorization Act (SARA) Title III:**

**Section 302 Extremely Hazardous Substances (40 CFR 355):**

**Components:**

**Concentration:**

Ethylene Glycol (107-21-1)

**Section 311/312 Hazard Class (40 CFR 370):**

Immediate Hazard: No  
 Delayed Hazard: No  
 Fire Hazard: Yes  
 Pressure Hazard: No  
 Reactive Hazard: No

**Section 313 Toxic Chemicals (40 CFR 372):**

**Components:**

**Reporting Threshold: 1.0%**

Glycol Ether EB (111-76-2)  
 Sodium 2-Biphenylate (132-27-4)  
 Ethylene Glycol (107-21-1)

**Comprehensive Environmental Response and Liability Act (CERCLA):**

**Section 304 Hazardous Substances (40 CFR 302):**

**Components:**

**Reporting Qty:**

Ethylene Glycol (107-21-1)  
 Phosphoric Acid (7664-38-2)

**OSHA Air Contaminants Standard (20 CFR 1910.1000):**

The following components of this product are listed as having limits for air contaminants:

Glycol Ether EB (111-76-2)  
 Dipropylene Glycol Methyl Ether (34590-94-8)  
 Silica, Crystalline Quartz (14808-60-7)

**State Regulations**

**California Proposition 65**

The product contains the following chemicals known to state of California to cause cancer and or birth defects based on maximum impurity levels of components:

Silica Crystalline Quartz (14808-60-7)  
 Sodium 2-Biphenylate (132-27-4)  
 Arsenic Trace Amounts  
 Ethylene Oxide Trace Amounts  
 Formaldehyde Trace Amounts  
 Nickel Trace Amounts  
 Lead Trace Amounts  
 1,4 Dioxane(123-91-1) Trace Amounts

**Pennsylvania, Massachusetts & New Jersey Hazardous Substance List Right to Know:**

The following components in this product are listed as hazardous at levels which require reporting.

Glycol Ether EB (111-76-2)

### International Regulations

**Canadian Environmental Protection Act (CEPA):**

The components for this product are included on the Canadian Domestic Substances List. (DSL)

**Canadian Workplace Hazardous Materials Information System (WHIMS):**

Class B3- Flammable Liquid Flash Point 127°F

Class D2B- Skin/Eye Irritation

---

## Section 16 - Other Information

---

**Prepared By:** SDS Coordinator

**Revision Date:** 1/1/17

**Disclaimer:** This material safety data sheet and the information it contains is offered to you in good faith as a guide to the safe use of the product and believed to be accurate to the best of our knowledge. Not all information in this data sheet is supported by specific testing and the evaluations are based on information from similar products, the ingredients and technical literature. The data contained herein is provided for your guidance only when handling the specific material designated in this MSDS and does not relate to any process or to use with any other materials. We recommend testing to determine the suitability of this product for your particular purpose prior to use. No responsibility is accepted that the information is sufficient, correct, and complete in all circumstances, as to the safety and health of individuals, disposal of materials and protection of the environment. It is the user's obligation to consider this MSDS as a supplement to other information required to make an independent determination to assure compliance to applicable laws and regulations when handling this material. The data in this document is provided without any representation or warranty expressed or implied regarding its accuracy or correctness. No warranty, either expressed or implied of merchantability or fitness or of any nature is made with respect to any product referred to herein. Manufacturer does not assume responsibility and expressly disclaims liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the products referred to herein. Manufacturer urges persons receiving this data to make their own determination as to the information's suitability and completeness for their particular application.