SAFETY DATA SHEET

1. Identification

REORDER # SA2000		
BURNISHINE ALL-PURPOSE MIST SPRAY ADHESIVE		
04-24-2014		
BURNISHINE		
LAKE VILLA, IL 10595 United States		
1-800-818-8275		
1-866-836-8855		
1-952-852-4646		
02		
03-05-2014		
Adhesive		
None known.		
Flammable aerosols	Category 1	
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2A	
Reproductive toxicity (fertility)	Category 2	
Specific target organ toxicity, single exposure	Category 3 narcotic effects	
Specific target organ toxicity, repeated	Category 2	
	BURNISHINE ALL-PURPOSE MIST SPF 04-24-2014 BURNISHINE LAKE VILLA, IL 10595 United States 1-800-818-8275 1-866-836-8855 1-952-852-4646 02 03-05-2014 Adhesive None known. Flammable aerosols Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity (fertility) Specific target organ toxicity, single exposure	

OSHA defined hazards

Label elements



exposure

Aspiration hazard Not classified.

Signal word	Danger		
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.		
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	Not classified.		
Environmental hazards	Hazardous to the aquatic environment, acute Category 2 hazard		

Category 1

Hazardous to the aquatic environment, Category 2 long-term hazard

Supplemental information

Hazard statement Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Collect spillage.

Avoid release to the environment.

Prevention

Response

43.35% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 43.35% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Hazardous components

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	10 - 20
Butane		106-97-8	10 - 20
Dimethyl Ether		115-10-6	10 - 20
n-Hexane		110-54-3	10 - 20
Cyclohexane		110-82-7	2.5 - 10
Isobutane		75-28-5	2.5 - 10
Propane		74-98-6	2.5 - 10
Other components below reportal	ble levels		10 - 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. Wash clothing separately before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Dry chemical powder. Alcohol resistant foam. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
6 Accidental release more	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the MSDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.
7. Handling and storage	
Precautions for safe handling	Do not handle or store near an open flame, heat or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in well-ventilated areas. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
		300 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
,		300 ppm	
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3	
		800 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
US. AIHA Workplace Environment	al Exposure Level (WEEL) Guid	es	
Components	Туре	Value	
Dimethyl Ether (CAS 115-10-6)	TWA	1880 mg/m3	
		1000 ppm	

Biological limit values					
ACGIH Biological Exposur	e Indices				
Components	Value	Determinant	Specimen	Sampling	Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*	
* - For sampling details, ple	ase see the source doc	ument.			
Exposure guidelines					
US - California OELs: Skir	n designation				
n-Hexane (CAS 110-54 US ACGIH Threshold Limi			absorbed thro	ugh the skin	l.
n-Hexane (CAS 110-54	4-3)	Can be	absorbed thro	ugh the skin	I.
Appropriate engineering controls	Explosion-proof ger	neral and local exha	ust ventilation.	Provide eye	ewash station.
Individual protection measure	s, such as personal pr	otective equipmer	nt		
Eye/face protection	Wear safety glasse	Wear safety glasses with side shields (or goggles).			
Hand protection	Wear protective glo	ves.			
Other	Wear appropriate c	hemical resistant clo	othing.		
Respiratory protection	limits (where applic	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.			
Thermal hazards	Wear appropriate the	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				

9. Physical and chemical properties

Appearance	
Color	Not available.
Form	Aerosol.
Physical state	Gas.
Flash point	-56.92 °F (-49.40 °C) estimated
Melting point/freezing point	Not available.
Odor	Not available.
рН	Not available.
Solubility(ies)	Not available.
Vapor density	Not available.
Vapor pressure	240.4 psig @70F estimated
Viscosity	Not available.
Other information	
Specific gravity	0.683 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion

Information on likely	routes of exposure
Ingestion	Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia. However, ingestion is not likely to be a primary route of occupational exposure.
Inhalation	No adverse effects due to inhalation are expected.

Skin contact

Eye contact

Acute toxicity

Symptoms related to the physical, chemical and toxicological characteristics

Causes skin irritation.

Causes serious eye irritation.

If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause central nervous system effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Acute toxicity	Expected to be a low hazard for usual industrial or commercial handling by trained perso	
Product	Species	Test Results
Fast Tack General Mist Adhe	esive (CAS Mixture)	
Acute		
Dermal	D-14:	
LD50	Rabbit	106.1008 ml/kg, estimated
	Rat	8570.7695 mg/kg, estimated
Inhalation		
LC50	Mouse	6914.0825 mg/l, 2 Hours, estimated
		4708.1904 mg/l, 15 Minutes, estimated
		3675.6191 mg/l, 30 Minutes, estimated
		722.9669 mg/l, If <1L: Consumer Commodity Hours, estimated
	Rat	34642.1836 mg/l, 15 Minutes, estimated
		6690.3911 mg/l, 4 Hours, estimated
		265.7825 mg/l, 8 Hours, estimated
		98.4066 mg/l/4h, estimated
NOEL	Monkey	12748.7188 mg/l, 6 Hours, estimated
Oral	,	
LD50	Mouse	7255.1392 mg/kg, estimated
	Rabbit	28328.9121 mg/kg, estimated
	Wistar rat	279.2023 mg/kg, estimated
Other		
LD50	Mouse	6880.6362 mg/kg, estimated
	Rat	29177.7188 mg/kg, estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg
		20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
		50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Other		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
utane (CAS 106-97-8)		~ ~ ~
Acute		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
LOOU		

Components	Species	Test Results	
Cyclohexane (CAS 110-82-7)			
Acute			
Inhalation			
NOEL	Monkey	1243 mg/l, 6 Hours	
Oral		1000 //	
LD50	Mouse	1300 mg/kg	
	Rat	29820 mg/kg	
Dimethyl Ether (CAS 115-10-6) Acute			
Inhalation			
LC50	Mouse	494.36 mg/l, 15 Minutes	
		385.94 mg/l, 30 Minutes	
	Rat	308.5 mg/l, 4 Hours	
Isobutane (CAS 75-28-5)			
Acute			
Inhalation			
LC50	Mouse	52 mg/l, If <1L: Consumer Commodity	
		Hours	
n-Hexane (CAS 110-54-3)			
Acute			
Inhalation LC50	Mouse	48000 mg/l, 4 Hours	
	Mouse	48000 mg/l, 4 nours	
Oral LD50	Rat	24 mg/kg	
	Wistar rat	49 mg/kg	
Propane (CAS 74-98-6)		-3 mg/kg	
Acute			
Inhalation			
LC50	Rat	> 1442.847 mg/l, 15 Minutes	
		658 mg/l/4h	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye	Causes serious eye irritation.		
irritation			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause sk	in sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a ca	arcinogen by IARC, ACGIH, NTP, or OSHA.	
Reproductive toxicity	Suspected of damaging fertility or the un	born child.	
Specific target organ toxicity - single exposure	Narcotic effects.		
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
12. Ecological information	1		
Ecotoxicity	Toxic to aquatic life with long lasting effects.		
Product	Species	Test Results	

Product	Species		Test Results
Fast Tack General Mis	st Adhesive (CAS N	/lixture)	
Algae	IC50	Algae	5127.6924 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia	74264.6172 mg/L, 48 Hours, estimated
Fish	LC50	Fish	15.6375 mg/L, 96 Hours, estimated

Components		Species	Test Results
Acetone (CAS 67-64-1)			
	EC50	Daphnia	13999 mg/L, 48 Hours
Aquatic			-
	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
	LC50	Rainbow trout, donaldson trout	4740 - 6330 mg/l, 96 hours
		(Oncorhynchus mykiss)	
Cyclohexane (CAS 110-82-7) Aquatic			
	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours
Persistence and degradability	No data is ava	ilable on the degradability of this product.	<u> </u>
Bioaccumulative potential	No data availa	• • •	
Partition coefficient n-octan			
Dimethyl Ether	or water (log r	0.1	
Acetone		-0.24	
Propane		2.36	
Isobutane Butane		2.76 2.89	
Cyclohexane		3.44	
n-Hexane		3.9	
Mobility in soil	No data availa	ble.	
Other adverse effects		rse environmental effects (e.g. ozone deplocrine disruption, global warming potential)	
	potential, end	serine disruption, global warming potential)	are expected from this component.
13. Disposal consideration	าร		
Disposal instructions	Collect and re	claim or dispose in sealed containers at lic	ensed waste disposal site.
Local disposal regulations	Dispose in acc	cordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
US RCRA Hazardous Waste	U List: Referen	ice	
Acetone (CAS 67-64-1)		U002	
Cyclohexane (CAS 110-8	2-7)	U056	
Waste from residues / unused products	Dispose of in a product residu Disposal instru	accordance with local regulations. Empty on es. This material and its container must be actions).	containers or liners may retain some e disposed of in a safe manner (see:
Contaminated packaging	Since emptied emptied	containers may retain product residue, fol	low label warnings even after container is
14. Transport information			
DOT			
UN number	UN1950		
UN proper shipping name	Aerosols, flam	mable	
Transport hazard class(es)	2.1		
Subsidiary class(es)	Not available.		
Packing group	Not available.		
	Read safety in	structions, SDS and emergency procedure	es before handling.
Labels required	None		
Special provisions	N82		
Packaging exceptions Packaging non bulk	306 Nono		
Packaging hon bulk	None None		
		s of section 173.306 as a limited quantity a	and may be shipped as a limited quantity
Until 12/31/2020, the "Consum mark for packages of UN 1950	ner Commodity - D Aerosols. Limit	• ORM-D" marking may still be used in plac and quantities require the limited quantity d ner Commodity ORM-D" marking and both	ce of the new limited quantity diamond amond mark on cartons after 12/31/20
IATA		, - · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	2.1
Subsidiary class(es)	-
Packaging group	Not available.
Environmental hazards	Yes

Labels required ERG Code	2.1 10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, MARINE POLLUTANT
Transport hazard class(es)	2.1
Subsidiary class(es)	-
Packaging group	Not available.
Environmental hazards	
Marine pollutant	Yes
Labels required	None
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and	Not applicable.

DOT

the IBC Code





Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302	.4)
Acetone (CAS 67-64-1)	LISTED
Cyclohexane (CAS 110-82-7)	LISTED
n-Hexane (CAS 110-54-3)	LISTED
US. OSHA Specifically Regulated Substances (29	9 CFR 1910.1001-1050)
Not listed.	

SARA 304 Emergency releas	se notification		
Not regulated.			
Superfund Amendments and Re	authorization Act of 1986 (SA	NRA)	
Hazard categories	Immediate Hazard - Yes		
	Delayed Hazard - Yes Fire Hazard - Yes		
	Pressure Hazard - Yes		
	Reactivity Hazard - No		
SARA 302 Extremely hazardous substance	No		
SARA 311/312 Hazardous chemical	No		
Other federal regulations			
Clean Air Act (CAA) Section	112 Hazardous Air Pollutant	s (HAPs) List	
n-Hexane (CAS 110-54-3 Clean Air Act (CAA) Section	8) 112(r) Accidental Release Pl	revention (40 CFR 68.130)	
Butane (CAS 106-97-8)			
Dimethyl Ether (CAS 115 Isobutane (CAS 75-28-5)	-		
Propane (CAS 74-98-6)			
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Adm Chemical Code Number	. , .	ential Chemicals (21 CFR 1310.02(b)	and 1310.04(f)(2) and
Acetone (CAS 67-64		6532	
Acetone (CAS 67-64		Exempt Chemical Mixtures (21 CFR ' 35 % weight/volumn	1310.12(C))
DEA Exempt Chemical I	•		
Acetone (CAS 67-64	-1)	6532	
Food and Drug Administration (FDA)	Not regulated.		
US state regulations			
US. New Jersey Worker and	Community Right-to-Know A	Act	
Butane (CAS 106-97-8)		500 lbs	
Cyclohexane (CAS 110-8 Dimethyl Ether (CAS 115		500 lbs 500 lbs	
Isobutane (CAS 75-28-5)		500 lbs	
n-Hexane (CAS 110-54-3	3)	500 lbs	
Propane (CAS 74-98-6)	ordous Cubatanasa	500 lbs	
US. Pennsylvania RTK - Haz Acetone (CAS 67-64-1) E			
(CAS 106-97-8) Cyclohe			
(CAS 110-82-7) Dimethyl	Ether		
(CAS 115-10-6) Isobutan	e		
(CAS 75-28-5) n-Hexane (CAS 110-54-3	3)		
Propane (CAS 74-98-6)	,		
US. California Proposition 6	5		
	Nater and Toxic Enforcement A I as carcinogens or reproductive	ct of 1986 (Proposition 65): This mate e toxins.	rial is not known to contain any
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Chem	ical Substances (AICS)	No
Canada	Domestic Substances List (D	SL)	Yes
Canada	Non-Domestic Substances L		No
China	Inventory of Existing Chemic	al Substances in China (IECSC)	No
Europe	European Inventory of Existir Substances (EINECS)	ng Commercial Chemical	No
Europe	European List of Notified Che		No
Japan		w Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-05-2014
Revision date	04-24-2014
Version #	02
Further information	Not available.
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	GHS: Classification